

SUN DELTA CORP

JINBOCHO MITSUI BLDG, 1-105 KANDA JINBOCHO, CHIYODA-KU TOKYO 101-8101 JP

VS(f)

Polycarbonate (PC), furnished as sheets or film

Color	Min Thk (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str
NC, BK	0.07-0.1	VTM-0	-	-	80	80	80
	0.1-0.33	VTM-0	3	4	130	120	130
	0.4	V-0	3	3	130	120	130
	3.0	V-0	2	3	130	120	130

Comparative Tracking Index (CTI): **3**

Dimensional Stability (%): -

High-Voltage Arc Tracking Rate
(HVTR): **3**High Volt, Low Current Arc Resis (D495): **7**

Dielectric Strength (kV/mm): -

Volume Resistivity (10^x ohm-cm): -**(f) - May be replaced by any digit 000-999, except 560 and 160.**

ANSI/UL 94 small-scale test data does not pertain to building materials, furnishings and related contents. ANSI/UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in the components and parts of end-product devices and appliances, where the acceptability of the combination is determined by UL.

Report Date: 2006-02-24

Last Revised: 2011-07-19

Underwriters Laboratories Inc®

